



## Odvlaživač vazduha | T3/DG

### KARAKTERISTIKE

Visok stepen vlažnosti vazduha, osim što izaziva osećaj nelagodnosti, može predstavljati opasnost za Vas i Vaš dom.

Ekonomičan, energetski efikasan i lak za upotrebu.

Elektronske kontrole.

Diskretna kontrola relativne vlažnosti i smanjenje prisustva alergena kao što su grinje, buđ i trulež.

Režim rada Isušivanje (za model DG): pametan i ekonomičan način da osušite svoj veš.

Kondenzovana voda sprovodi se neposredno u odvod ili u rezervoar za vodu.

Uređaj se automatski isključuje kada je rezervoar pun.

Automatsko restartovanje: ukoliko jedinica neočekivano prestane sa radom usled prekida u napajanju, automatski će se restartovati nakon dolaska struje tako da sva prethodna podešavanja ostanu na snazi.

Pametni režim rada Odvlaživanje (za model DG): Jedinica će automatski kontrolisati vlažnost vazduha u prostoriji tako da bude u prijatnom opsegu od 45% do ~55% u skladu sa sobnom temperaturom.

Za lakši prenos, model T3 je opremljen velikom ergonomskom ručicom, a model GD poseduje točkove.



T3



DG

### TEHNIČKE SPECIFIKACIJE\*

MODEL		CDT-105E3	CDT-165E3	CDG-205E	CDG-255E	CDG-305E
Uklanjanje vlage	L / dan	10	16	20	25	30
Ulazna snaga	kW	0,22	0,41	0,263	0,324	0,605
Energetski faktor (EEV)	L / kWh	1,89	1,63	3,17	3,22	2,07
Veličina prostorije	m <sup>2</sup>	80	120	150	190	230
Početna struja	A	6,48	10,5	5,5	5,5	9,5
Način upravljanja		ELEKTRONSKA KONTROLA				
Vrsta rashladnog sredstva		R134A	R134A	R134A	R134A	R410A
Projektovani pritisak	MPa	1,7/0,7	1,7/0,7	1,7/0,7	1,7/0,7	4,2/1,5
Zapremina rezervoara za vodu	L	1,4	3,5	4,7	4,7	4,7
Protok vazduha	m <sup>3</sup> / h	120	130	210	220	220
Nivo zvučnog pritiska	dB(A)	43	45	47	50	50
Opseg relativne vlažnosti	%	35 - 80	35 - 80	35 - 85	35 - 85	35 - 85
Temperatura okoline	°C	5 - 35	5 - 35	5 - 35	5 - 35	5 - 35
Dimenzije (Š × D × V)	mm	335 × 280 × 435	386 × 320 × 495	400 × 254 × 562	400 × 254 × 562	400 × 254 × 562
Težina	Kg	10,5	13,5	15	15,5	15,5
Napajanje	V-Ph-Hz	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50

Napomena:

Š × D × V = širina × dubina × visina

\*Preliminarni podaci





## Dehumidifier | T3/DG

### FEATURES

High humidity levels that can be dangerous to you and your home beyond feelings of discomfort

Cost-effective, energy-efficient and user-friendly.

Electronic control.

Discreet control of the relative humidity and reduction of allergens such as dust mites, mold and dry rot.

Dryer mode (for DG series): A smart and cost – effective way to dry your laundry.

Condensed water is led directly into the drain or into a water tank.

Automatic switch off when the tank is full.

Auto-Restart: If the unit breaks off unexpectedly due to the power cut, it will restart with the previous function setting automatically when the power resumes.

Smart dehumidifying mode (for DG series): The unit will automatically control room humidity in a comfortable range 45%~55% according to the room temperature.

For easy carrying T3 series has a big handle and DG series has wheels.



T3



DG